



50 TON

Compact and Versatile

Four Available Workstations
 Punch Assembly Designed for Optional Tooling
 Dedicated Coper Notcher Station
 Electric Stroke Control
 ANSI B11.5-1988R(02) Compliant
 ETL/UL Approved Controls

The Edwards 50 Ton JAWS Ironworker is the ideal Ironworker for the small shop that needs a powerful, versatile tool for all kinds of tasks. Standard features include a Punch Assembly with Pedestal Die Table, Flat Bar Shear, Angle Shear, and a dedicated Coper Notcher station. The Punch Assembly quickly converts to an open tooling station designed to accept optional Tooling Accessories.

PUNCH

Rating: 50 Tons
 Max. Capacity: 1" Dia. in 5/8" A36
 Stroke: 1-7/8"
 Throat Depth: 7"
 Open Height: 8-1/8"
 Shut Height: 6-1/4"
 Work Height: 36-9/16"

ANGLE SHEAR

Max. Capacity: 3" x 3" x 3/8"
 4" x 4" x 1/4"
 Work Height: 39-7/8"

FLAT BAR SHEAR

Max. Width: 1/2" x 10"
 3/4" x 4"
 Max. Round: 3/4"
 Max. Square: 3/4"
 Work Height: 34-1/2"

COPER NOTCHER

Max. Capacity: 2" x 3" x 5/16"
 Work Height: 39-1/2"

GENERAL SPECIFICATIONS

Standard Motor: 5 HP 3~ 208 V or 230 V
 1725 RPM 14 A
 Optional Motors: 5 HP 3~ 460 V
 1725 RPM 7 A
 5 HP 3~ 575 V
 1725 RPM 6 A
 5 HP 1~ 208 V or 230 V
 1725 RPM 23 A
 Hydraulic Pump: 3-1/2 GPM - 1 Stage
 Valve Pressure: 2500 PSI
 Reservoir: 7 Gallons
 Cylinder: 2-1/2" Ram

DIMENSIONS

Height: 54-1/2"
 Width: 36-3/4"
 Depth: 36-1/8"
 Shipping Weight: 2020 lb

CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM