



60 TON

Our Best Value

Four Loaded Workstations
Dedicated Coper Notcher Station
Electric Stroke Control
ANSI B11.5-1988R(02) Compliant
ETL/UL Approved Controls

The Edwards 60 Ton JAWS Ironworker is a robust machine featuring a dedicated Coper Notcher station, adding strength and stability to this great tool. Standard features include a Punch Assembly with Pedestal Die Table, 14" wide Flat Bar Shear, Angle Shear and Coper Notcher.

PUNCH

Rating: 60 Tons
Max. Capacity: 1" Dia. in 3/4" A36
Stroke: 1-1/4"
Throat Depth: 8-7/8"
Open Height: 8-1/8"
Shut Height: 6-7/8"
Work Height: 36-9/16"

ANGLE SHEAR

Max. Capacity: 3" x 3" x 1/2"
4" x 4" x 3/8"
Work Height: 39-7/8"

FLAT BAR SHEAR

Max. Capacity: 3/8" x 14"
1/2" x 12"
3/4" x 4"
Max. Round: 7/8"
Max. Square: 7/8"
Work Height: 34-1/2"

COPER NOTCHER

Max. Capacity: 2-1/2" x 4" x 3/8"
Work Height: 39-1/2"

GENERAL SPECIFICATIONS

Standard Motor: 5 HP 3~ 208 V or 230 V
1725 RPM 14 A
Optional Motors: 5 HP 3~ 460 V
1725 RPM 7 A
5 HP 3~ 575 V
1725 RPM 6 A
5 HP 1~ 208 V or 230 V
1725 RPM 23 A

Hydraulic Pump: 3-1/2 GPM - 1 Stage
Valve Pressure: 2500 PSI
Reservoir: 7 Gallons
Cylinder: 2-1/2" Ram

DIMENSIONS

Height: 56-1/8"
Width: 46-1/8"
Depth: 36-1/8"
Shipping Weight: 2550 lb



CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM